


Venstar Programmable Thermostat T2800



STANDARD FEATURES:

- Up to 3-Occupied, 1-Unoccupied periods per day, with copy command for easy programming
- Accepts humidification/dehumidification control module (Venstar part number ACC0430)
- Auto changeover, 3-stage heat, 2-stage cool for use with gas/electric, heat pump, electric & hydronic heat
- Configurable for manual changeover, also configurable programmable or non-programmable
- Adjustable deadbands and timers
- 3 configurable outputs for maximum flexibility (MISC1, MISC2, MISC3)
- Extra 6th and 7th outputs (beyond our standard thermostat)
- Smart Fan (keeps the fan from running during unoccupied periods)
- Smart recovery
- Display shows both heating an cooling setpoints and room temperature simultaneously
- All programming and setpoints stored in non-volatile memory, and are never lost in power failure
- Service filter and service UV lamp indicators
- Red/Green LED shows whether thermostat is calling for heating or cooling
- 5-minute compressor time guard and adjustable cycle limit, both defeatable for servicing equipment
- Outdoor sensor ready with high and low temperature of the day
- Thermoglow backlit electro-luminous display and backlit color coded keys and legends
- Accepts accessory IR Remote Control system (Venstar part number ACC0431)
- Accepts accessory EZ Programmer (Venstar part number ACC0432)
- For accessory locking cover use (Venstar part number ACC0620)

MODEL:	T2800	QUANTITY:		DATE:		
JOB NAME:						
LOCATION:						
BUYER:				BUYER P.O.#:		
ENGINEER:						